

RF5108WKK1-433 Wireless Key Kit



Product Features:

- ▶ Ideal for those applications where only a few wireless keys and zones are required
- ▶ 433 MHz wireless receiver
- ▶ Supports up to eight wireless keys (without taking up a zone slot) and eight wireless detectors
- ▶ Small, compact design
- ▶ Includes an internal antenna
- ▶ KEYBUS compatible with PowerSeries™ control panels
- ▶ Two on-board, fully programmable (50 mA) outputs
- ▶ LED switch plate (single-gang) provided
- ▶ WS4939 four-button wireless key included
- ▶ UL/ULC and CE approved

RF5108WKK1-433



Useful for those applications where coverage of a large area is not required, the RF5108WKK1-433 wireless key kit can simultaneously support up to eight wireless detection devices and eight wireless keys without taking up a zone slot.

The RF5108-433 wireless receiver of the kit easily expands any DSC hardwired system by adding coverage to areas that are difficult or impossible to reach with conventional wiring. The RF5108WKK1-433 wireless key kit is ideal for small- to mid-size installations.



www.dsc.com
1-888-888-7838

RF5108WKK1-433 Wireless Key Kit



Easy Installation

To help reduce installation times, the wireless key receiver features an internal antenna and connection to the control panel via a four-wire KEYBUS.

Value Added

The RF5108WKK1-433 features two on-board 50 mA programmable outputs that can be used to trigger the LED switch plate (single-gang) that is included with the kit or be programmed to perform other tasks, such as activating garage door openers, turning on lights or opening powered gates.

WS4939 Wireless Key

The WS4939 four-button wireless key included with the kits adds convenience and value to any DSC security system. These multi-purpose devices include activation delays and can be used to arm/disarm any PowerSeries™ security system from a distance. To trigger the arm/disarm function, you must press and hold the appropriate button for one second, and for the panic function, three seconds. An integrated LED indicator signifies to the user that a transmission has been sent to the security system.

Compatibility

The RF5108WKK1-433 is compatible with all DSC 433 MHz devices and the following control panels:

- Power432™ PC580/585
- Power632™ PC1555/1565
- Power832® PC5010
- Power864™ PC5020

Specifications

Dimensions	4 1/4" x 3 1/8" x 1" (108 mm x 78 mm x 25 mm)
Voltage	12 Vdc
Current Draw	40 mA (Typical)
Operating Environment	32° to 120° F (0° to 49° C)
Relative Humidity	5% to 93%

Ordering Information:

RF5108WKK1-433	Wireless Key Receiver
WS4939	4-Button Wireless Key